

# VeriShield™ VS120F Passive Earmuff

# Honeywell

HOWARD  
LEIGHT

## PRODUCT INFORMATION

Rev.:  
01

Date:  
2019.06.19

### SPECIFICATIONS

<b>ARTICLE</b>	VeriShield Passive Folding Earmuff, VS120F	
<b>MODEL NO</b>	1035141-VS	
<b>REGION</b>	EMEA/AUS	
<b>BARCODES</b>	Box	7312550351413
	Case	17312550351410
<b>WEIGHT</b>	227g	
<b>ACCESSORIES</b>	Hygiene Kit	1035137-VS
	Cool Pads	1000365
<b>SALES UNITS</b>	Box	1 EA
	Case	10 boxes
<b>VOLUME</b>	Box	L135*W105*H125mm 1.77dm <sup>3</sup>
	Case	L540*W275*H157mm 23.31dm <sup>3</sup>
<b>MATERIAL</b>	Box	Cardboard
	Case	Corrugated cardboard



POS.	PART LISTING	MATERIAL	COLOR
1	Ear Cup	ABS	NCS 8500-N
2	Rim	PP	NCS 8500-N
3	O-ring	Silicon	NATURAL
4	Foam Insert	PU foam	PMS 7621C
5	Ear Cushion	PVC/PU Foam	NCS 9000-N
6	Wire Guide	POM	NCS 9000-N
7	Headband	PU/Foam/Steel	NCS 9000-N

# VeriShield™ VS120F Passive Earmuff



**HOWARD  
LEIGHT**

## PRODUCT INFORMATION

Rev.:  
01

Date:  
2019.06.19

### CUSTOM TARIFFS

39269099

### COUNTRY OF ORIGIN

China

### TEMPERATURE OPERATION RANGE

0°C to +55°C/32°F to +131°F

### PRODUCT MARKING

“Honeywell HOWARD LEIGHT” - cup

“VS120F” – cup

### SNR

VeriShield™ VS120F Passive Earmuff is tested according to EN 352-1:2002 at Michael & Associates Inc.

Frequency Hz	125	250	500	1000	2000	4000	8000	SNR
Mean Value, dB	21.9	23.0	29.7	36.7	39.3	37.6	39.0	
Standard Deviation, dB	2.8	2.8	3.3	3.9	2.9	2.7	3.9	32 dB
Assumed Protection, dB	19.1	20.3	26.3	32.8	36.4	34.9	35.2	

H=36 dB M=29 dB L=24 dB

### SLC80

VeriShield™ VS120F Passive Earmuff is tested according to AS/NZS 1270:2002 at Michael & Associates Inc.

Frequency Hz	125	250	500	1000	2000	4000	8000	SLC80
Mean Attenuation, dB	20.3	21.3	28.8	35.9	38.8	36.7	39.7	
Standard Deviation, dB	4.0	4.2	3.6	2.9	2.7	2.5	2.7	31 dB
Mean-Minus-Std Deviation, dB	16.3	17.1	25.2	33.0	36.1	34.2	37.0	

Class 5

### For more information

[www.honeywellsafety.com](http://www.honeywellsafety.com)

### Honeywell Industrial Safety

9680 Old Bailes Road, Fort Mill, SC 29707

Phone: 803-835-8000

Fax: 401-232-3110