



# Reims

131ZA2T01



## Hi-vis fleece

Our soft and double-sided Reims fleece will keep you warm and well in winter. It has a high pilling resistance and can be zipped into the Brighton rain jacket (132Z) with our I.L.S. system. The windbreaker in the front offers extra protection against chilly winds.



# Hi-vis fleece

**Reims - 131ZA2T01**

## European Standards

- » EN ISO 20471 : 2013 / Class 3
- » RIS 3279 TOM 2016 only for Hi-Vis orange
- » EN 14058 : 2004 / Class 1 x x x x
- » CE
- » EN ISO 13688 : 2013

## Exterior

- » Straight collar
- » Zip closure
- » 1 inset chest pocket with zip closure
- » 2 inset pockets with zip closure
- » Round inset sleeves
- » Elastic at end of sleeves
- » Elastic drawstring in hem
- » Back length 76 cm (L)

## Interior

- » Fixed windbreaker lining in front
- » 1 inside pocket

## Fabric

100% polyester double sided fleece;  $\pm 285 \text{ g/m}^2$

## Sizes

XS - XXXL

## Colour

- » FC1 Hi-Vis Orange
- » FY1 Hi-Vis Yellow

## Combining products

199A - 199A - 4448 - 6361 - 6361 - 6575 - 6580 - 6580

## I.L.S.

132Z - 403Z

## Packaging

5 pieces per box

## Wash and care instructions



### SIOEN head office

Fabriekstraat 23

B-8850 Ardooie

Belgium

T: +32 (51) 740 800

F: +32 (51) 740 962

[www.sioen-ppc.com](http://www.sioen-ppc.com)



**Discover  
our products**

© 2017 Sioen Apparel - Protection through Innovation, Flexothane®, Siopor® and the SIOEN logo are trademarks of the Sioen Industries Group.

Please note that all information given in this document is intended to be useful and informative and is correct to the best of our knowledge at time of print. No liability can be accepted for inaccuracies or omissions. The right is reserved to amend this information without prior notice. All our technical files, style descriptions, presentations, designs and drawings, give the latest update of the standards and design or style features of each product. However, delivered products may comply with previous standards, design or style features. For that Sioen disclaims any liability whatsoever. Contact our sales for full information if specific requirements are needed.